


VENERA TOUCH PANEL

VENERA PANEL Model: VEN-ZIG-2G





OVERVIEW

This product is a wall switch with two touch buttons for smart control over lights, curtains, and scenes. It offers customizable backlit color and finishes for an easy combination with interior schemes.

KEY BENEFITS

- Compatibility with TIS solutions
- Improved energy efficiency
- Scene compatibility & TIS App controllability
- + Applicable in home, hotel & office rooms

KEY FEATURES

- Operating on ZigBee 3.0 protocol
- Equipped with internal energy meter
- Delicate touch buttons with backlit
- ★ Programmable for scenes & presets







TIS VENERA TOUCH PANEL Venera Panel

Model: VEN-ZIG-2G





PRODUCT SPECIFICATIONS			
4	Power supply	Input voltage Output power Protection	110-230 VAC 50/60 Hz 220 V Internal protection fuse
		Current consumption	10-30 mA / 12 V
<u>.</u>	Output	Number of channels Nominal voltage Nominal current per channel	2 110 / 230 V AC 50/60 Hz 8 A / 230 VAC
1	Output switching current	Max switching current	10A/230 VAC resistive 6A/230 VAC florescent
<u>.</u>	Output service life	Mechanical endurance	> 10,000,000 OPS
Ţ	Output switching times	Operating time Releasing time Max. operating frequency	8 mS (at nomi. Volt) 5 mS (at nomi. Volt) 25 cycle/min
TISEEE	TISBEE	ZigBee signal Protocol standard	2.4 GHz ZigBee 3.0
(}	Reaction time		approx. 30ms
\$ 0	Mounting	Wall mount	To US, EU, UK junction boxes
†‡†	Operation	Touch buttons Backlit	2 control buttons LED indicators
ۿ	Weight	Without packaging	150g
+	Dimensions	$Length \times Width \times Height$	85mm × 42mm × 109mm
	Housing	Materials Internal parts color IP rating	Fireproof PC/ Optional front cover Black / White IP 50
B	Temperature range	Operation Storage Transport	-1060°C -2050°C -2575°C
8	Air humidity		<80% non-condensing



TIS VENERA TOUCH PANEL Venera Panel

Model: VEN-ZIG-2G





